Venom[™] 1715 & 2015

17 inch & 20 inch, 175 rpm, Low-Speed Buffers



Reliable, simple and powerful

www.etjsm.com





All-metal construction.



Optional solution tank.



Easy-to-use, fingertip controls.



Venom™ 1715 & 2015

17 inch & 20 inch, 175 rpm, Low-Speed Buffers

Simple	Rugged	Affordable
• Easy-to-use, fingertip controls	• 3-year parts warranty	• Best value in the
 Hook-mounted pad driver storage 	 2-year warranty on labor 	 Pad driver include

- Universal clutch plate
- Safety lock-out switch
- 2-year warranty on labor
- All-steel, triple planetary gear box
- 1.5 hp, 66-frame motor
- All-metal construction
- CSA approved
- Designed for heavy, daily use

- the industry
- Pad driver included
- High cleaning productivity rate
- Backed by the most extensive, hassle-free warranty in the business

Technical Specifications

Description	Venom™ VN1715	Venom™ VN2015
Deck Size	17 in (43.2 cm)	20 in (50.8 cm)
Pad Driver	16 in (40.6 cm)	19 in (48.3 cm)
Pad/Brush Speed	175 rpm	175 rpm
Voltage	110 V	110 V
Horsepower	1.5 hp (1.1 kW)	1.5 hp (1.1 kW)
Motor, Heavy-duty	66-frame	66-frame
Gear Box, All-steel	Triple planetary	Triple planetary
Sound Level	63 dB A	63 dB A
Power Cable, Safety Yellow	50 ft (15.2 m)	50 ft (15.2 m)
Wheels, Non-marking Grey	(2) 5 in (12.7 cm)	(2) 5 in (12.7 cm)
Amp Draw	13 amps	13 amps
Weight	101 lbs (45.8 kg)	109 lbs (49.4 kg)
Shipping Weight	120 lbs (54.4 kg)	123 lbs (55.8 kg)
Dimensions (L x W x H)	27 in x 17 in x 48 in	27 in x 20 in x 48 in
	(65.6 cm x 43.2 cm x 122 cm)	(65.6 cm x 50.8 cm x 122 cm)
Optional Solution Tank	2.5 gal (9.46 L)	2.5 gal (9.46 L)
Optional Deck Sizes	15 in and 13 in	15 in and 13 in
	(38 cm and 33 cm)	(38 cm and 33 cm)

Specifications are subject to change without notice.





9435 Winnetka Avenue North Brooklyn Park, MN 55445 Phone: 800.989.2235 Fax: 800.989.6566

©2019 Nilfisk, Inc. Form L3352V 12-19

